

PROTECH™ ALUMINUM KEY-LOCK CARABINERS



Ideal for rescue and rope access, this anodized carabiner's patented key-lock design does not hang up when unclipping from your harness or web. An optimized D-shape maximizes its strength, and its wide gate opening fits over 1-inch (25-mm) diameter railings, unusual for a carabiner this compact and light. Safety indicators etched on the gate augment easy one-hand operation. Manual-Lock and Auto-Lock versions are available with a removable keeper pin for use with lanyards or for terminating escape or RIT lines. Every carabiner is proof loaded. Serial numbers on every carabiner.

Patented

ProTech	Major Axis	Minor Axis	Major Axis, Gate Open
300161	26 kn	9 kn	11 kn
300165	26 kn	9 kn	11 kn
300169	26 kn	9 kn	11 kn
300182	26 kn	9 kn	11 kn
300189	29 kn	8 kn	11 kn
300193	26 kn	9 kn	11 kn
300153	29 kn	8 kn	11 kn

OPTION	ITEM	PRODUCT WEIGHT	GATE OPENING	INTERIOR LENGTH	GATE / COLOR	NFPA RATING	3 SIGMA MBS	PRICE
Screw-Lock, Brite	300161	2.6 OZ (74 G)	1 IN (25 MM)	3.53 IN (89 MM)	SCREW-LOCK / BRITE	TECHNICAL USE	26 KN (5,845 LBF)	
Screw-Lock, Black	300165	2.6 OZ (74 G)	1 IN (25 MM)	3.53 IN (89 MM)	SCREW-LOCK / BLACK	TECHNICAL USE	26 KN (5,845 LBF)	
Screw-Lock, Orange	300169	2.6 OZ (74 G)	1 IN (25 MM)	3.53 IN (89 MM)	SCREW-LOCK / ORANGE	TECHNICAL USE	26 KN (5,845 LBF)	
Manual-Lock, Slate	300182	2.8 OZ (79 G)	1 IN (25 MM)	3.53 IN (89 MM)	MANUAL-LOCK / SLATE	TECHNICAL USE	26 KN (5,845 LBF)	
Manual-Lock, Orange w/Keeper	300189	3.6 OZ (102 G)	1 IN (25 MM)	3.53 IN (89 MM)	MANUAL-LOCK W/ KEEPER / ORANGE	TECHNICAL USE	29 KN (6,519 LBF)	
Auto-Lock, Red	300193	2.8 OZ (79 G)	1 IN (25 MM)	3.53 IN (89 MM)	AUTO-LOCK / RED	TECHNICAL USE	26 KN (5,845 LBF)	
Auto-Lock, Red w/Keeper	300153	3.6 OZ (102 G)	1 IN (25 MM)	3.53 IN (89 MM)	AUTO-LOCK W/ KEEPER / RED	TECHNICAL USE	29 KN (6,519 LBF)	
Keeper Pin Replacement Set (ProTech)	300000	3X PINS, 3X SCREWS, 1X HEX WRENCH	NA	NA	NA	NA	NA	