



**STORM  
SURGE**

[WWW.TNTRESCUE.COM](http://WWW.TNTRESCUE.COM)



# INDEX

WELCOME	PG 1
FOREVER WARRANTY	PG 2
CUTTERS	PG 3-4
COMBI NATION CUTTER / SPREADER	PG 5
SPREADERS	PG 6-8
RAMS	PG 9-10
ACCESSORIES	PG 11-12
ISO	PG 13





Welcome to TNT Rescue Systems, Inc, the premier manufacturer of Powered Hydraulic Rescue Tools. The employees and distributors are delighted with your interest in our products and look forward to a long and mutually beneficial relationship.

Blanton & Company began as an OEM manufacturer of Industrial hydraulic pumps. Entry into the rescue tool world came by way of one of our early customers, with the Blanton design of the first true 2 tool simultaneous operation pump. Owner and President Tom Blanton, noted a lack of customer service in the rescue tool market, creating the initial vision of what would become TNT Rescue Systems, Inc.

TNT Rescue Systems Inc's vision is simple: design, build, and distribute the highest quality hydraulic rescue tools, provide a Forever Warranty and support the customer with the highest level of service. The dedication to service is shown everyday by the family of TNT Rescue Systems, Inc. From employees at the factory, management, or our dealers we have current and retired firefighters throughout our organization and fully understand the expectations of tool performance on the street.

TNT Rescue Systems, Inc. understands the service you need from you rescue tools and your tool manufacturer. Dedication to our customers continues with our Forever Warranty. Our warranty is the most comprehensive in the industry, providing coverage for our products. Whether you're a dealer or end user we are committed to providing you with exceptional customer service. Our customer-focused method of doing business has been the standard at TNT Rescue Systems Inc, ( Blanton & Company ) since its start in 1986.

TNT Rescue Systems, Inc. is 100% owned and operated with our only facility solely located in Ashippun, Wisconsin.

To that end, TNT Rescue Systems, Inc. is a ISO 9001:2015 registered company and builds tools to exceed the minimum performance standard of NFPA 1936 & EN 13204





TNT RESCUE SYSTEMS STORM-SURGE SERIES BATTERY-OPERATED  
EXTRICATION TOOLS ARE POWERED BY THE MILWAUKEE M18 OR DEWALT® 20V PLATFORMS,  
MAKING THEM THE LONGEST-RUNNING PORTABLE RESCUE TOOLS ON THE MARKET.  
THE END-USER BENEFITS FROM THE PRICE AND AVAILABILITY USING THESE OEM NON-PROPRIETARY BATTERIES.  
THE TOOLS FEATURE AN ALL-NEW WELL BALANCED COMPACT ALUMINIUM DESIGN, WITH TOOL SPEEDS THAT  
ARE UNMATCHED UNDER BOTH LOADED AND UNLOADED CONDITIONS WITH NO DEGRADATION IN POWER.  
WITH THIS NEW DESIGN, IT MAKES IT POSSIBLE TO DO RELIEF CUTS IN TIGHT POSITIONS WHERE OTHER MANUFACTURERS CANT.  
THE BATTERY TERMINAL IS LOCATED ON THE TOP OF THE TOOL BETWEEN THE CARRY HANDLE AND CONTROL VALVE,  
PROVIDING BETTER PROTECTION AND SAFETY.

CONTACT YOUR LOCAL DEALER FOR MORE INFORMATION ON THE TNT FOREVER WARRANTY OR  
ALTERNATIVELY VISIT OUR WEBSITE: [WWW.TNTRESCUE.COM](http://WWW.TNTRESCUE.COM)



**STORM  
SURGE**





# STORM SURGE



## ESLC-29-18V

LENGTH	32.99 IN	837.90 MM
HEIGHT	11.69 IN	296.83 MM
WIDTH	10.5 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	51.40 LBS	23.31 KG
INCL. BATTERY	53.75 LBS	24.38 KG
MAX. BLADE OPENING	8.00 IN	203.00 MM
MAX. CUT REACH	5.08 IN	129.15 MM
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
NFPA CUT TEST	A8, B9, C9, D9, E9, F5	
IP RATING	54	



## ESLC-29-20V

LENGTH	32.99 IN	837.90 MM
HEIGHT	11.69 IN	296.83 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	51.40 LBS	23.31 KG
INCL. BATTERY	54.60 LBS	24.76 KG
MAX. BLADE OPENING	8.00 IN	203.00 MM
MAX. CUT REACH	5.08 IN	129.15 MM
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
NFPA CUT TEST	A8, B9, C9, D9, E9, F5	
IP RATING	54	





# STORM SURGE



## EBFC-320-18V

LENGTH	35.81 IN	909.69 MM
HEIGHT	11.81 IN	299.91 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	61.55 LBS	27.91 KG
INCL. BATTERY	63.90 LBS	28.98 KG
MAX. BLADE OPENING	8.6 IN	218.44 MM
MAX. CUT REACH	4.75 IN	120.65 MM
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
NFPA CUT TEST	A9, B9, C9, D9, E9, F6	
IP RATING	54	



## EBFC-320-20V

LENGTH	35.81 IN	909.69 MM
HEIGHT	11.81 IN	299.91 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	61.55 LBS	27.91 KG
INCL. BATTERY	64.75 LBS	29.37 KG
MAX. BLADE OPENING	8.6 IN	218.44 MM
MAX. CUT REACH	4.75 IN	120.65 MM
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
NFPA CUT TEST	A9, B9, C9, D9, E9, F6	
IP RATING	54	



# 4



**BUILT TO  
RESCUE**



# STORM SURGE



## EBFCC-28-18V

LENGTH	36.21 IN	919.79 MM
HEIGHT	11.74 IN	298.13 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	52.75 LBS	23.92 KG
INCL. BATTERY	55.08 LBS	24.98 KG
MAX. BLADE OPENING	10.12 IN	257.06 MM
MAX. CUT REACH	5.55 IN	140.96 MM
MAX. SPREAD DISTANCE	17.00 IN	431.80 MM
MAX. SPREAD FORCE	286,000 LBF	1,272 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
NFPA CUT TEST	A8, B7, C8, D8, E9, F5	
IP RATING	54	



## EBFCC-28-20V

LENGTH	36.21 IN	919.79 MM
HEIGHT	11.74 IN	298.13 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	52.75 LBS	23.92 KG
INCL. BATTERY	55.95 LBS	25.37 KG
MAX. BLADE OPENING	10.12 IN	257.06 MM
MAX. CUT REACH	5.55 IN	140.96 MM
MAX. SPREAD DISTANCE	17.00 IN	431.80 MM
MAX. SPREAD FORCE	286,000 LBF	1,272 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
NFPA CUT TEST	A8, B7, C8, D8, E9, F5	
IP RATING	54	



**BUILT TO RESCUE**





# STORM SURGE



## ES100-24-18V

LENGTH	32.43 IN	823.77 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	46.85 LBS	21.25 KG
INCL. BATTERY	49.20 LBS	22.31 KG
MAX. SPREAD DISTANCE	23.50 IN	596.9 MM
MAX. SPREAD FORCE RANGE	64,476- 242,368 LBF	28.6- 1,078 KN
MAX. PULL DISTANCE	14.25 IN	361.95 MM
MAX. PULL FORCE	14,368 LBF	63.91 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



## ES100-24-20V

LENGTH	32.43 IN	823.77 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	46.85 LBS	21.25 KG
INCL. BATTERY	50.05 LBS	22.70 KG
MAX. SPREAD DISTANCE	23.50 IN	596.9 MM
MAX. SPREAD FORCE RANGE	64,476- 242,368 LBF	28.6- 1,078 KN
MAX. PULL DISTANCE	14.25 IN	361.95 MM
MAX. PULL FORCE	14,368 LBF	63.91 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	





# STORM SURGE



## ES100-28-18V

LENGTH	34.80 IN	883.99 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	48.20 LBS	21.86 KG
INCL. BATTERY	50.55 LBS	22.92 KG
MAX. SPREAD DISTANCE	27.50 IN	698.50 MM
MAX. SPREAD FORCE RANGE	56,128- 228,126 LBF	249- 1.014 KN
MAX. PULL DISTANCE	18.25 IN	463.55 MM
MAX. PULL FORCE	11,168 LBF	49.67 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



## ES100-28-20V

LENGTH	34.80 IN	883.99 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	48.20 LBS	21.86 KG
INCL. BATTERY	51.40 LBS	23.31 KG
MAX. SPREAD DISTANCE	27.50 IN	698.50 MM
MAX. SPREAD FORCE RANGE	56,128- 228,126 LBF	249- 1.014 KN
MAX. PULL DISTANCE	18.25 IN	463.55 MM
MAX. PULL FORCE	11,168 LBF	49.67 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



**BUILT TO  
RESCUE**

# 7



# STORM SURGE



## ES100-32-18V

LENGTH	37.17 IN	944.16 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	49.45 LBS	22.43 KG
INCL. BATTERY	51.80 LBS	23.49 KG
MAX. SPREAD DISTANCE	31.50 IN	700.10 MM
MAX. SPREAD FORCE RANGE	50,592 - 201,420 LBF	225 - 895 KN
MAX. PULL DISTANCE	22.25 IN	565.15 MM
MAX. PULL FORCE	9,339 LBF	41.54 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



## ES100-32-20V

LENGTH	37.17 IN	944.16 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	49.45 LBS	22.43 KG
INCL. BATTERY	52.65 LBS	23.88 KG
MAX. SPREAD DISTANCE	31.50 IN	700.10 MM
MAX. SPREAD FORCE RANGE	50,592 - 201,420 LBF	225 - 895 KN
MAX. PULL DISTANCE	22.25 IN	565.15 MM
MAX. PULL FORCE	9,339 LBF	41.54 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



**BUILT TO RESCUE**



# STORM SURGE



## ER-40-18V

CLOSED LENGTH	25.50 IN	647.70 MM
EXTENDED LENGTH	41.00 IN	1041.40 MM
HEIGHT	10.75 IN	273.00 MM
WIDTH	8.10 IN	205.70 MM
WEIGHT		
EXCL. BATTERY	41.25 LBS	18.71 KG
INCL. BATTERY	43.60 LBS	19.77 KG
MAX. PUSH FORCE	37,005 LBF	164.60 KN
MAX. PULL FORCE	8,293 LBF	36.88 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



## ER-40-20V

CLOSED LENGTH	25.50 IN	647.70 MM
EXTENDED LENGTH	41.00 IN	1041.40 MM
HEIGHT	10.75 IN	273.00 MM
WIDTH	8.10 IN	205.70 MM
WEIGHT		
EXCL. BATTERY	41.25 LBS	18.71 KG
INCL. BATTERY	44.45 LBS	20.16 KG
MAX. PUSH FORCE	37,005 LBF	164.60 KN
MAX. PULL FORCE	8,293 LBF	36.88 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	





# STORM SURGE



## ETLS-40-18V

CLOSED LENGTH	21.50 IN	546.10 MM
EXTENDED LENGTH	42.25 IN	1073.15 MM
HEIGHT	10.75 IN	273.00 MM
WIDTH	8.10 IN	205.70 MM
WEIGHT		
EXCL. BATTERY	38.75 LBS	17.57 KG
INCL. BATTERY	41.10 LBS	18.64 KG
1 <sup>ST</sup> STAGE STROKE	12.95 IN	329.00 MM
1 <sup>ST</sup> STAGE MAX. PUSH FORCE	38.067 LBF	169.33 KN
2 <sup>ND</sup> STAGE STROKE	8.70 IN	221.00 MM
2 <sup>ND</sup> STAGE MAX. PUSH FORCE	13.088 LBF	58.21 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



## ETLS-40-20V

CLOSED LENGTH	21.50 IN	546.10 MM
EXTENDED LENGTH	42.25 IN	1073.15 MM
HEIGHT	10.75 IN	273.00 MM
WIDTH	8.10 IN	205.70 MM
WEIGHT		
EXCL. BATTERY	38.75 LBS	17.57 KG
INCL. BATTERY	41.95 LBS	19.02 KG
1 <sup>ST</sup> STAGE STROKE	12.95 IN	329.00 MM
1 <sup>ST</sup> STAGE MAX. PUSH FORCE	38.067 LBF	169.33 KN
2 <sup>ND</sup> STAGE STROKE	8.70 IN	221.00 MM
2 <sup>ND</sup> STAGE MAX. PUSH FORCE	13.088 LBF	58.21 KN
POWER SOURCE OPTION	DEWALT 20V	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



10





# STORM SURGE

## RAM BASE EXTENSION-KIT



### 6 INCH RAM BASE EXTENSION

ASSEMBLED LENGTH 10.35 IN 262.73 MM

#### MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 48.75 IN 123.82 CM

ETLS-40 WITH EXTENSION 50.00 IN 127.00 CM

### 12 INCH RAM BASE EXTENSION

ASSEMBLED LENGTH 16.35 IN 415.29 CM

#### MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 54.75 IN 139.07 CM

ETLS-40 WITH EXTENSION 56.00 IN 142.24 CM

### 18 INCH RAM BASE EXTENSION

ASSEMBLED LENGTH 22.35 IN 567.69 CM

#### MAXIMUM EXTENDED LENGTH

ER-40 WITH EXTENSION 60.75 IN 154.31 CM

ETLS-40 WITH EXTENSION 62.00 IN 157.48 CM



# 11



**STORM  
SURGE**

**R-KIT**



**XR-KIT**



**570220-M18 - 8AH**



**570221-M18 DUAL  
RAPID CHARGER**



**570222-20V/60V - 9AH**    **570223-DCB118 SINGLE  
FAST CHARGER**



**12**



**BUILT TO  
RESCUE**



## ***ISO 9001-2015***

The International for Standardization (ISO) is a network of national standards instituted in 157 countries. Each ISO member is the leading standards organization in its country. These members devise new standards, work to advance them, and team up with the ISO Central Secretariat to guide the technical groups that develop them.

They award certification only after registered, independent auditors review a company's process against strict ISO standards, and verify that the company has met established requirements, in both policy and practice.

TNT Rescue Systems Inc. is certified as an ISO 9001:2015 registered firm. This means you can be sure that TNT Rescue Systems Inc. products are designed and manufactured to the high standards our industry - and the ISO - demands. Certification covers all that we do to enhance customer satisfaction by meeting both customer and regulatory requirements, while continually improving performance.



***PERFORMANCE, QUALITY  
AND SERVICE  
GUARANTEED!***



MADE IN THE USA

**FOR MORE DETAILED SPECIFICATIONS PLEASE VISIT OUR  
WEBSITE:**

***WWW.TNTRESCUE.COM***

*email: contactus@tntrescue.com*

**RESCUE**



**YouTube**

